WOOD HEATER Lugano MC90/44





The original stove-fireplace created by Piazzetta entirely in hand finished majolica (ceramic). The generous heating capacity of 12.2kW will ensure even the most spacious home will be cosy and warm. Other sizes and firebox openings are available by special order.

This wood-burning product is also available with Multifuoco and Multifuoco System Plus as an option. This will ensure uniform heat flow from floor to ceiling, or to a ducting system is desired.

Enjoy the natural flame of a wood heater with all the efficiency and benefits of fingertip control usually only available in pellet heaters.

COLOURS









Bianco

Nero Opaco


Rosso Lava


Terra Cotta


(Nero Opaco, Rosso Lava & Terra Cotta by order only)

WHAT YOU NEED TO KNOW

Wood Heaters like other heaters & stoves need to be installed by a licensed plumber or trained installer. Regular maintenance and cleaning will enhance the performance and life of your heater.







Work	A :-	1	- 34	0	80
MC4586	136	75	101	16	108
MC 7981	HT	*	110		191
MC toler	110	700	125	(8)	100
MC 120/46	114	109	129	28	10
MC464 BL	126	866	140		100
MC 9688 St.	111	94.6	136	*	146
BC 105/H BL	110	1146	128	20	- 09
MC 100763 RL	114	1426	tig	19	146

TECHNICAL DATA

Firebox heat output kW

Nominal heat output (min-max) kW

Room heating capacity (min-max) m³

Nominal thermal efficiency %

Nominal consumption (min – max) *1

Heat Diffusion

Optional Multifuoco (Forced Ventilation)

Optional Air Intake

Dimensions W x D x H cm

Stove weight kg

Flue cm

12.2kW

11 – 12.2 kW 205 – 350m3 79.3%

3.2 kg/hr Natural radiation, convection

4 power levels and ductable up to 10 metres

Kit to draw air from outside

100 x 53 x 125 260 kg 20

GENERAL CHARACTERISTICS

Cladding

Stove

Firebox, Baffle Plate/Brazier

Door

Door Handle

Standard Flue Outlet Position

· Primary and secondary air

Preset tertiary air

LCD Digital Controls

Ceramic Glass

Glass Cleaning System

Remote Stove SMS Texting or WIFI

Installation *2

Majolica Steel Aluker

Cast Iron, outer door in steel Painted Steel – detachable

Top

Manually adjustible

Pre-heated

Optional with Multifuoco Resistant up to 750°

Continuous air flow Optional with Multifuoco

Wall

*1 Consumption varies depending on type of wood and moisture content

*2 Please refer to instruction manual for detailed installation specifications

www.piazzetta.com.au





The modern and efficient stoves-Fireplace

Four models with clean lines and contemporary finishes with large tiled panels available in five colors to suit any environment. The hearth of the design delivers high performance and high heat output.

MULTIFUOCO SYSTEM

Perfect warmth from the floor to the ceiling.

If you install the Multifuoco® kit - the extraordinary patented ventilation system with remote control – you can ensure that heat is evenly spread throughout the room as well as in adjacent rooms with a ducting system of up to 10 metres.

MULTIFUOCO SYSTEM PLUS

Innovative electronic control

Optional forced ventilation kit with four electronic controlled power levels and LCD remote control. Warm air ducting up to 10 m

TERTIARY AIR SYSTEM

Better performances.

The preheated tertiary air system, in many models, fully optimizes combustion and ensures high efficiency with low emission into the atmosphere.

GREAT PERFORMANCES

Excellent heat output.

The particular structure of the stove and the large radiant surface area ensure a high heat output and therefore an ideal level of comfort in your home.











